

C E 0085



CERT

EC type examination certificate
EU-Baumusterprüfbescheinigung

CE-0085BU0343

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Guard Sound Industry Co., Ltd. No. 52-1, Lane 11, Hua Cheng Rd., TW- Hsin Chuang City 24252
Distributor <i>Vertreiber</i>	Guard Sound Industry Co., Ltd. No. 52-1, Lane 11, Hua Cheng Rd., TW- Hsin Chuang City 24252
Product Category <i>Produktart</i>	accessories for gas appliances/pressure equipment: Multi functional control (4104)
Product Description <i>Produktbezeichnung</i>	Multifunctional control with 2 solenoid valves and gas flow control for water and room heaters
Model <i>Modell</i>	DV-1; DV-2
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK
Test Reports <i>Prüfberichte</i>	type testing: 17/136/4104/142 from 29.06.2017 (EBI)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 13611 (01.09.2016) DIN EN 126 (01.06.2012) DIN EN 161 (01.04.2013)
Validity / File no. <i>Gültigkeit / AZ</i>	21.04.2018 until 10.07.2027 / 17-0442-GEA

7028/04-A DE



10.07.2017 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EC Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
gases of the 2.& 3. family acc to EN 437	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
DV-1; DV-2	outlet pressure: 13...20 mbar inlet pressure range: max. 65 mbar ambient temperature range: 0...+60 °C	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
DV-1	with manual flow control (2 on/off valves)
DV-2	with automatic flow control (1 on/off valve + 1 modulating valve)

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

connection: at the input side G 1/4...G 1/2 according to DIN EN ISO 228-1; at the outlet side G 1/2...G 3/4 according to DIN EN ISO 228-1 (or metric thread for DV-2)

class of valve: C

group: 1

open-/close time: <1,5 s/ < 1 s

mounting position: any